

Compliance checklist for declaration of compliance in accordance with MOC Light UAS 2511-01 for ENAC project _____

Doc. Section	Means	Reference doc.	Remarks
1	<p>Applicability of this MoC:</p> <ul style="list-style-type: none"> — UAS operated in an operation in the specific category classified up to SAIL II according to SORA; — UA dimension: recommended for UAS whose characteristic dimension is equal to or less than three (3) meters, in consideration of the limited performance attributed to the FTS. Higher dimensions can be accepted by the competent authority when the kinetic energy or speed are sufficiently low (typically below 34 kJ or 35 m/s respectively) — UA design: no specific restrictions. For lighter-than-air, normally the ground risk is considered smaller than for heavier-than-air (with equal UA dimension and scenario)⁷. However, the prescriptions to determine the ground risk buffer as indicated in 2.5 are not applicable for lighter-than-air and the criteria to determine such buffer would have to be re-determined in agreement with the authority; 		
2.1	The FTS should be segregated from the UAS flight control system architecture. Such segregation needs to be simply verifiable and comply with paragraphs 2.1.1, 2.1.2 and 2.1.3		
2.1	The FTS can be manually and/or automatically activated. In the case of manual activation, the system will include a ground and an air (i.e.: on-board) segments.		
2.1	The remote pilot should have means to detect if the FTS is not available due to the failure of any of the elements contributing to its proper functioning.		
2.1	<p>A design checklist document should be made available and include:</p> <ul style="list-style-type: none"> — a high level description of the FTS architecture; — the FTS installation on the UAS; 		

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022

Doc. Section	Means	Reference doc.	Remarks
	— assessment as per chapters 2.1.1, 2.1.2, 2.1.3 with evidence of compliance with each of these chapters;		
2.1.1	<p>Segregation of the air segment</p> <p>The air segment of the FTS should be segregated from the UAS flight control system architecture and from any other element of such architecture whose failure may induce a loss of control, unless such failure would only lead to crash in the operational volume or ground risk buffer.</p>		
2.1.1	For example, the FTS air segment may use the same power supply of the UAS, as a loss of a power supply could be considered a failure leading to a crash in the operational volume. In such a case, erroneous operation of onboard power supply (out of range voltage, inverted polarity) should not result in loss of containment and loss of the FTS.		
2.1.1	If the FTS is activated from ground, the receiver of the FTS signal installed onboard should be independent from the receiver utilized for command and control.		
2.1.1	If the FTS is automatically activated, its activation should be triggered by systems which are not utilized for the control of the UAS operation within the operational volume.		
2.1.1	For example, positioning information utilized to trigger the FTS should be provided by different systems (not implying different technology ¹¹) with respect to the ones utilized during normal operation of the UAS.		
2.1.2	<p>Segregation of the ground segment (where applicable)</p> <p>The unit(s) utilized to trigger the FTS should be segregated from the Command Unit (CU) utilized for UAS control during operation. The segregation should be such that correct functioning of the FTS would be unaffected, if CU operation would be lost or function erroneously.</p>		
2.1.3	<p>Frequency and frequency diversity</p> <p>When using radio frequencies for the initiation of flight termination, the frequency band utilized by the FTS should be separated from the frequency band utilised for UAS control.</p>		

[Digitare qui]

Doc. Section	Means	Reference doc.	Remarks
2.1.3	Where the specific operational volume includes emitting sources of high power radio frequencies ¹³ , the frequencies used by the FTS should not be superimposed with such frequencies.		
2.1.3	The flight manual (see chapter 2.3) should provide the relevant information on the frequency bands and avoidance of areas which could cause interference.		
2.2	Tests Adequate performance of the FTS should be verified with the following set of tests as per 2.2.1 to 2.2.4.		
2.2	A test procedures and result document should be made available to the authority and cover such set of tests.		
2.2	The documentation should contain date and time of test and test configuration, including FTS and utilised test equipment.		
2.2	Where any test is not passed (FTS not activated, not correctly activated or erroneously activated), the document should record the root cause analysis and investigation of the failure and the change of FTS and/or test equipment configuration that may have been necessary on the basis of such investigation.		
2.2	The series of tests shall not be restarted without the failure event having been recorded and analyzed.		
2.2	Tests shall be considered passed only when bench, ground, flight and end-to-end tests executed consecutively as per chapters below will have been passed.		
2.2	Any failure will require analysis of the root cause, possible modification of the system, justification of such modification and recording in the documentation, re-execution of tests starting from bench tests.		
2.2.1	Bench tests on FTS These tests should be performed on the uninstalled FTS in a controlled environment.		

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022

Doc. Section	Means	Reference doc.	Remarks
2.2.1	Where manually activated, the operator should trigger the termination function with the ground unit and observe that the correct termination signal is received by the FTS receiver		
2.2.1	Where automatically activated, correct activation of the termination signal should be tested providing as input to the FTS those conditions which would cause its triggering in flight.		
2.2.1	The applicant should perform a number of tests considered adequate on the base of the FTS complexity. At least ten (10) activation tests should be performed. Bench tests are considered passed when the full set of tests is passed consecutively.		
2.2.2	Ground integration tests after installation of the FTS on the UAS These tests need to demonstrate proper activation of the FTS as installed on the UAS and that the desired effect on the UAS is obtained.		
2.2.2	If the FTS is activated from ground during real operation, the tests should be such to test the maximum operational distance of the UAS from the antenna transmitting the command of flight termination. The ground FTS unit needs to be connected with the antenna as in the real operational case.		
2.2.2	Where automatically activated, correct activation of the termination signal should be tested providing in input to the FTS those conditions which would cause its triggering in flight. In this case, the activation should be checked for a set of conditions covering uniformly the whole activation envelope, while limiting the granularity of such checks.		
2.2.2	Where the FTS deploys a parachute, it is possible to not install the parachute; it is sufficient to ascertain that proper termination of flight would be triggered and that the signal causing parachute deployment is correctly received (without actually causing parachute deployment).		

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022

Doc. Section	Means	Reference doc.	Remarks
2.2.2	The number of tests performed should be adequate to the complexity of the FTS as installed on the UAS. At least ten (10) activations should be performed. Ground tests can be considered passed when the full set of tests is passed consecutively.		
2.2.3	Flight test Flight tests need to be carried out in low risk scenarios (typically: a VLOS operation in a test location over a controlled ground area, where the probability of encountering another aircraft is negligible and with very low risk in adjacent areas).		
2.2.3	Flight tests are not considered necessary for UAS with MTOW < 900 grams, unless they are used in lieu of the ground tests.		
2.2.3	Flight tests need to demonstrate proper activation of the on-board segment of the FTS, however, a representative non-destructive configuration may be arranged (e.g. digital recording of the FTS signal which would normally interrupt power connection to engines when FTS is actuated, avoiding that such signal actually commands power interruption during tests).		
2.2.3	It should be demonstrated that each activation from ground, respectively each test case in which the FTS is supposed to be automatically actuated, would result in a correct flight termination.		
2.2.3	The following minimum scenarios should be tested: — UAS flying straight and levelled towards or away to / from the antenna transmitting the termination signal, at the minimum and maximum height expected during the operation (excluding climb and descent segments). At least 10 activations should be triggered: — 5 at minimum height, 2 of which testing the maximum distance of operation at that height, the other 3 with approximate equal distribution as depicted below;		

[Digitare qui]

Doc. Section	Means	Reference doc.	Remarks
	— 5 at maximum height, 2 of which testing the maximum distance of operation at that height, the other 3 with approximate equal distribution as above;		
2.2.3	— UAS flying straight and levelled in a direction perpendicular to the one of the tests above, same heights as above, same distribution as above;		
2.2.3	In case of automatic FTS activation, the conditions / scenario set for activation should lead to automatic termination approximately with the distances and patterns as above.		
2.2.4	End-to end activation tests These tests aim to assess the proper functioning of the FTS system integrated on a particular UAS throughout the entire life of the UAS.		
2.2.4	The tests should be carried out using the same FTS-UAS combination that has been subject to the tests specified in 2.2.2 and 2.2.3.		
2.2.4	The number of activations (triggering of the FTS and observation of proper operation) should be equal to the number of expected activations of the FTS for its entire life (accounting for pre-flight checks, maintenance checks, return to service checks).		
2.2.4	The lapse of time in which such tests are performed will depend on the organization of the tests (i.e. the activations can be performed in a rapid sequence, considering that the unit might need to rest long enough to avoid adverse effects).		
2.2.4	The information on these maximum number of activations should be provided in the maintenance manual.		
2.3	Flight Manual The following should be reflected in the UAS flight manual , either as supplement of the manual or integrated:		
2.3	— Limits and conditions for the FTS, including its frequency band; — Proper procedures to ensure that the FTS will be operated appropriately and it will work as intended throughout the life of the installed system;		

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022

Doc. Section	Means	Reference doc.	Remarks
2.3	A procedure requiring at least one pre-flight check (on-ground) of the FTS installed on the UAS, which needs to be carried out before the first flight of the day on a given site of operation. This check is dedicated to minimize the possibility of latent failures. If the check fails the FTS needs to be replaced before flight, and re-checked. When the FTS is associated with means to reduce impact dynamics (i.e. a parachute), the deployment of such means can be avoided for the pre-flight check provided that all other elements in the chain contributing to proper functioning of the FTS are checked;		
2.3	The minimum extent of the ground risk buffer, defined according to point 2.5, should be specified in the flight manual.		
2.4	Maintenance Instruction Maintenance instructions should be established to ensure that the FTS will work as intended throughout the life of the installed system.		
2.4	These should include the necessary actions to be taken after reaching the maximum expected number of activations in accordance with 2.2.4.		
2.4	As part of maintenance, the in-service reliability of the FTS should be tracked by recording the following data:		
2.4	— Number of FHs accumulated by the UAS with FTS installed;		
2.4	— In case of FTS activations failures during pre-flight checks record the FH accumulated by the UAS at time of failed activation;		
2.4	— In case of FTS activations failures during flight, keep record of: <ul style="list-style-type: none"> — FH accumulated by the UAS at time of failed activation; — attempted activation distance between CU and UAS (where applicable); — specific location of the operation; — presence or not of high power emitters in the operational volume. 		
2.4	— In case of FTS activations during flight keep record of: <ul style="list-style-type: none"> — if activation was commanded or un-commanded; 		

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022

Doc. Section	Means	Reference doc.	Remarks
	<ul style="list-style-type: none"> — FH accumulated by the UAS at time of activation; — distance between the CU and UAS (where applicable); — specific location of the operation; — presence or not of high power emitters in the operational volume. 		
2.4	If the failure probability observed in service is higher than $10^{-2}/FH$ (accounting for statistical uncertainty), the operator should report to the competent authority.		
2.5	<p>Prescriptions for ground risk buffer definition</p> <p>The minimum extension of the ground risk buffer should be specified in the flight manual and its value should ensure that any termination event would end with the crash of the UAS only within the ground risk buffer.</p>		
2.5	<p>In order to determine such extension, the following factors need to be considered:</p> <ul style="list-style-type: none"> — T: Human and system latencies in the activation of the FTS; — D1: Distance travelled by the UAS during time T (projected on ground); — D2: distance travelled by the UAS after termination is effectively triggered onboard (as projection on ground of its trajectory). 		
2.5	<p>Conservatively and as a simple solution:</p> <ul style="list-style-type: none"> — T = 3 sec; — V = maximum UAS cruise speed, or maximum speed declared as part of the operational authorization complemented, for UAS beyond 1 m characteristic dimension, by possible maximum acceleration due to Flight Control System (FCS) failure determining an increase of speed during the latency of 3 sec. Worst expected wind conditions (intensity and direction) should also be considered; — $D1 = V \cdot T$; 		
2.5	— D2:		

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022

Doc. Section	Means	Reference doc.	Remarks
	<ul style="list-style-type: none"> — For rotorcraft / multirotors apply any of the following options: <ul style="list-style-type: none"> — Compute D2 as projection of a ballistic trajectory on ground, with a maximum of 0.8 drag. The projection should be perpendicular to the operational volume all along the perimeter of such volume. Velocity vector at termination: horizontal, oriented perpendicularly to the operational volume and at the maximum height of the operational volume. Modulus computed according to the above guidance for V; — Compute D2 as projection on ground of a glide trajectory with 9 degree incidence angle (same V in modulus and direction); — Determine D2 on the basis of tests (V in modulus and orientation as above defined) 		
2.5	<ul style="list-style-type: none"> — For Fixed wing apply any of the following options: <ul style="list-style-type: none"> — Determine D2 on the basis of tests (V as above defined); — Compute D2 as projection on ground of a glide trajectory with 9 degree incidence angle (V as above defined); 		
2.5	<ul style="list-style-type: none"> — When a parachute is deployed as part of the FTS: <ul style="list-style-type: none"> — D2 estimated as (maximum wind considered for the operation)x(height at termination)/(speed of descent with parachute). As a correction should be considered to account for speed at termination, for simplicity D2 as calculated above should be increased of 10%; — Determine D2 with tests (taking into account worst environmental conditions and maximum height of operation). 		
2.5	Ground risk buffer = D1 + D2		
2.5	Operational considerations might affect ground risk buffer and require a different one with respect to what above assessed, where		

[Digitare qui]

Doc. Section	Means	Reference doc.	Remarks
	so established by the competent authority for operational authorization.		
3	Means to reduce impact dynamics (optional) This MoC does not necessarily require integration in the FTS of means to reduce UAS impact dynamics ¹⁷ (typically a parachute).		
3	If such combination is intended, it should be ensured that they do not negatively impact the safety of the operation and the correct operation of the FTS.		
3	Correct integration of these means would require flight tests to verify correct deployment when triggering the FTS.		
3	Such tests could be integrated with the tests above prescribed for the FTS.		
3	This MoC does not address the performance of such means in terms of capability of reducing kinetic energy.		

*dichiaro che i documenti sopra riportati forniscono piena rispondenza alle indicazioni del **MOC Light UAS 2511-01** per quanto applicabili all'operazione oggetto del progetto **for ENAC project**_____*

*it is hereby declared that the above documents provide full compliance with the indications of **MOC Light UAS 2511-01** in so far as they are applicable to the operation covered by **for ENAC project**_____*

Operatore*

Operator *

FIRMA

Signature

DATA ,

Date,

* Il Richiedente della pertinente Autorizzazione Operativa

* the Applicant of the relevant Operational Authorisation

[Digitare qui]

Form ENAC MOC Light UAS 2511-01 20_maggio_2022